

TLS-3

TALKBACK LOUDSPEAKER STATION is a remote, 3-channel, selectable talkback speaker device, with the function to talk and/or listen on the given channel. TLS comes with built-in 5W quality speaker and amplifier to monitor the communication clearly. LEDs on panel indicate which channel is selected or unselected to monitor. Receive-only provides paging function to existing intercom system without having to install separate paging amplifier and speaker. TLS-3 has a gooseneck-mic socket and feedback control circuit, giving hands-free full-duplex communication without a headset.

Power Input: DC/24-30V; Max. 500mA
 Headset Mic Input: 200~600 Ohms,
 Dynamic Headphone Output: 200 Ohms ideal
 Audio Speaker Output: Max. 5W;
 94db SPL at one meter
 Dimension: 11.00 x 26.50 x 17.00 cm
 Net/ Gross Weight: 4.0/ 4.5 KG



The features of headsets are with thin, flexible cable without tugging on the headset and can be clasped out of the way with our optional clip. Comfortable ear-cushions can be washable with ordinary dish washing detergent. The microphone can be easy adjusted to be very close to the mouth.

SMH-075

SINGLE-EAR HEADSET

Microphone: Dynamic, 200hms
 Earphone fq.: 80Hz-110KHz
 Sensitivity: 90db
 Max. Power: 200mw
 Impedance: 200Ohm
 T.H.D.: <2%
 Connector: XLR-4pin/ 1.5M



DMH-075

DOUBLE-EAR HEADSET

Microphone: Dynamic, 200hms
 Earphone fq.: 80Hz-110KHz
 Sensitivity: 90db
 Max. Power: 200mw
 Impedance: 400Ohm
 T.H.D.: <2%
 Connector: XLR-4pin/ 1.5M



DMH-095

HEAVY DUTY DOUBLE-EAR HEADSET

Microphone: Dynamic, 200hms
 Earphone fq.: 30-10KHz
 Sensitivity: 90db
 Max. Power: 200mw
 Impedance: 200Ohm
 T.H.D.: <3%
 Connector: XLR-4pin/ 1.5M



BSP-1 BELTPACKS

is portable long-life comfort headset station. The easily control top panel for switching the microphone on and off, controlling listing level and signaling. The steel plate belt is elasticized for comfortable using. Compatible with all famous popular headset intercom.

Headphone Output: 9-4K Ohms acceptable, 200 Ohms ideal
 Microphone Input: 300-600 Ohms, Dynamic
 Sidetone Rejection: >50db
 Dimension: 93.98 x 109.22 x 63.50 mm



PS-30 POWER SUPPLY UNIT FOR 30 BELTPACKS

- * For 30 units BSP-1 beltpacks
- * Power supply: 110V-0.2A/220V-0.1A, 50-60Hz
- * Universal power input
- * Output: Max. DC24V/1.0A
- * Auto: Max. DC27V/1.7A
- * Dimension: 45 x 260 x 104 mm
- * Weight: 1.8kg



MPS-60 POWER SUPPLY UNIT FOR 60 BELTPACKS

The MPS-60 is highly regulated 27VDC, 3.8Amp (cont.) power supply capable of supplying up to 60 BSP-1 beltpacks with all signal lights lit. It may be rack mounted or used as a talbe-top unit.

Power Required: 90-240V AC, 0.05A (None Load),
 1.5A @3.85A DC output 50-60Hz

Power Output: 27V DC +/-0.5V, 0-3.8A
 Audio Termination: 200 Ohms unbalanced
 Dimension: 4.5 x 48 x 23 cm, 1U High
 Weight: 3.5 KG (7.75lbs)

