

POWER DISTRIBUTION BOX

POWER BOX

KUPO power distribution boxes are made of 1.2mm thickness steel material. The internal wiring consists 1.5mmsq (16AWG) silicon cable as standard. The sinking front panel for a better protection of each connector. The standard 2 hanging rings to make rigging easier on truss. Each side with an extra clamp hanging hole to fit limited space. The following is the range of power distribution boxes, other variations of power distribution boxes are available upon requested.

PDB-001

270(L) x 190(W) x 80(H)mm
With 6 channels stage 3 Pin female socket & PLS-5219SM 19 Pin connector (wired)



PDB-001D

295(L) x 190(W) x 80(H)mm
With 6 channels stage 3 Pin female socket & PLS-5219SM and PLS-5219SF 19 Pin connector (wired)



PDB-003

270(L) x 190(W) x 80(H)mm
With 6 channels Schuko female socket & PLS-5219SM 19 Pin connector (wired)



PDB-003D

295(L) x 190(W) x 80(H)mm
With 6 channels Schuko female socket & PLS-5219SM and PSL-5219SF 19 Pin connector (wired)



PDB-004

270(L) x 190(W) x 80(H)mm
With 6 channels CEE female socket & PLS-5219SM 19 Pin connector (wired)



PDB-005

340(L) x 190(W) x 80(H)mm
With 8 channels CEE female socket & KM16M with locking 16 Pin connector (wired)



PDB-005D

295(L) x 190(W) x 80(H)mm
With 6 channels CEE female socket & PLS-5219SM and PLS-5219SF 19 Pin connector (wired)



PDB-006

340(L) x 190(W) x 80(H)mm
With 8 channels Schuko female socket & KM16M with locking 16 Pin connector (wired)



CUSTOM DESIGN AVAILABLE

