

STROBE



E-45P/75P ZAP STROBE

Voltage: 100/240V, 50-60Hz, 45-75W
 Remote Trigger: 10V DC positive pulse ,
 1/4" mono microphone jack
 Lens color available in clear, yellow, blue,
 red and green
 Dimension Dia.: 2200 x L230 mm bracket
 radius 200 mm
 Weight: 2.4 KG



E-75A COMPACT STROBE

Voltage: 100/240V, 50-60Hz
 75W helical xenon lamp
 Flash Rate: 1-12 flash/sec.
 Dual 1/4" jacks for synchronous operation
 Weight: 3.25 KG
 Rugged extruded aluminum case
 Dimension: 220H x 300W x 130D mm



E-005 POINT STROBE
E-006 HANGING STROBE

Octagonal design breaks the light into
 infinite beams creating stunning sparkle
 6W per flash long life xenon tube
 Flash Rate: 0.3-1 flash/rate
 10 million flash life
 Voltage: 100/240V
 Dimension: 52 x 110 mm
 Weight: 130g



E-1800 1500W STROBE

E-1800D 1500W DMX DIMMABLE STROBE

Voltage: 230V, 50-60HZ
 Power Cons.: 2,700W
 Dimension: 125(W) x 220(D) x 4600(H) mm
 Weight: 3 KG
 Fuse: NFB 16A
 Remote Trigger: 10V DC positive pulse
 Standard DMX Control
 Dimmable Flash
 1500 per flash
 Canon Signal
 Tempered front glass
 Extruded Aluminum Case
 Easy lamp replacement
 Manual speed control on back
 Adjustable flash rate 1-12 fps (Hz)
 Sturdy hanging bracket
 Manual dimmable
 Meets CE (EMC and LVD) standard



E-75B STANDARD STROBE

Voltage: 100/240V, 50-60Hz
 75W helical xenon lamp
 Flash Rate: 1-12 flash/sec.
 Dual 1/4" jacks for synchronous operation
 Weight: 2.4 KG
 Rugged extruded steel case
 Dimension: 215H x 270W x 175D mm



E-035 MINI STROBE

35W per flash extra long life xenon tube
 Flash Rate: 1-10 flash/sec.
 10 million flash life
 Voltage: 100/240V
 Dimension: 135H x 97W x 55D mm
 Weight: 500g